



## Late Models Rules

Revised Mar 6, 2025

### Table of Contents

|   |          |
|---|----------|
| <b>PERSONAL EQUIPMENT.....</b>                  | <b>4</b> |
| <b>DRIVER SAFETY.....</b>                       | <b>4</b> |
| <b>ENGINE OPTIONS.....</b>                      | <b>4</b> |
| <b>OPTION # 1: RIVERHEAD RACEWAY CRATE.....</b> | <b>4</b> |
| CARBURETOR.....                                 | 5        |
| BASE PLATE.....                                 | 6        |
| BUTTERFLIES.....                                | 6        |
| THROTTLE SHAFT.....                             | 6        |
| CARBURETOR SPACER/GASKET.....                   | 6        |
| IGNITION SYSTEM.....                            | 6        |
| ENGINE OIL.....                                 | 7        |
| WATER PUMP/ALTERNATOR.....                      | 7        |
| <b>OPTION #2: LATE MODEL.....</b>               | <b>7</b> |
| ENGINE DISPLACEMENT.....                        | 7        |
| ENGINE BLOCK.....                               | 8        |
| PISTONS/RODS.....                               | 8        |
| CRANKSHAFT/BALANCER.....                        | 8        |
| OIL PAN.....                                    | 8        |
| CYLINDER HEAD.....                              | 8        |
| CAMSHAFT/VALVE LIFTERS/ROCKER ARMS.....         | 9        |
| INTAKE MANIFOLD.....                            | 9        |



|   |           |
|---|-----------|
| CARBURETOR.....                         | 9         |
| Carburetor Jets.....                    | 9         |
| Body of Carburetor.....                 | 9         |
| Venturi.....                            | 10        |
| Base Plate.....                         | 10        |
| Butterflies.....                        | 10        |
| Throttle Shaft.....                     | 10        |
| Spacer/Gaskets.....                     | 10        |
| FUEL FILTER.....                        | 10        |
| IGNITION SYSTEM.....                    | 11        |
| <b>OPTION #3: CHARGER.....</b>          | <b>11</b> |
| ENGINE DISPLACEMENT.....                | 11        |
| ENGINE BLOCK.....                       | 11        |
| INTERNAL CHANGES.....                   | 12        |
| CRANKSHAFT/BALANCER.....                | 12        |
| CYLINDER HEAD.....                      | 12        |
| CAMSHAFT/VALVE LIFTERS/ROCKER ARMS..... | 13        |
| INTAKE MANIFOLD.....                    | 14        |
| CARBURETOR.....                         | 14        |
| Carburetor Jets:.....                   | 14        |
| Body of Carburetor:.....                | 14        |
| Venturi.....                            | 15        |
| Base Plate:.....                        | 15        |
| Butterflies.....                        | 15        |
| Throttle Shaft.....                     | 15        |
| Spacer/Gaskets.....                     | 15        |
| FUEL FILTER.....                        | 16        |
| OIL PAN.....                            | 16        |
| IGNITION SYSTEM.....                    | 16        |
| ENGINE LOCATION.....                    | 16        |
| <b>WEIGHT RULES.....</b>                | <b>17</b> |



|   |           |
|---|-----------|
| <b>BATTERY.....</b>                             | <b>17</b> |
| <b>BRAKE COMPONENTS.....</b>                    | <b>18</b> |
| <b>CAR BODIES.....</b>                          | <b>18</b> |
| <b>EXHAUST SYSTEM.....</b>                      | <b>19</b> |
| <b>FUEL CELL.....</b>                           | <b>19</b> |
| <b>GAUGES.....</b>                              | <b>20</b> |
| ELECTRICAL SWITCHES.....                        | 20        |
| <b>HOOD.....</b>                                | <b>20</b> |
| <b>MIRRORS.....</b>                             | <b>20</b> |
| <b>RADIATOR AND FAN.....</b>                    | <b>20</b> |
| <b>REAR END.....</b>                            | <b>20</b> |
| <b>ROLL CAGE.....</b>                           | <b>21</b> |
| <b>SEATS.....</b>                               | <b>22</b> |
| <b>SPOILERS.....</b>                            | <b>22</b> |
| <b>STARTER.....</b>                             | <b>22</b> |
| <b>STEERING.....</b>                            | <b>22</b> |
| <b>SUSPENSION.....</b>                          | <b>23</b> |
| SPINDLES, WHEEL BEARINGS, AND HUBS.....         | 23        |
| FRONT SUSPENSION.....                           | 23        |
| REAR SUSPENSION.....                            | 23        |
| SHOCKS/SPRINGS.....                             | 23        |
| GROUND CLEARANCE.....                           | 24        |
| <b>TRANSMISSION, DRIVELINE, AND CLUTCH.....</b> | <b>24</b> |
| Transmission.....                               | 24        |
| Driveshaft.....                                 | 24        |
| Clutch.....                                     | 24        |
| <b>WHEELS AND TIRES.....</b>                    | <b>24</b> |
| <b>WINDSHIELD.....</b>                          | <b>25</b> |



## **PERSONAL EQUIPMENT**

1. All drivers must have a full-face Snell 2015 rated or better helmet in good condition.
2. No M rated helmets.
3. Fire suit gloves and shoes SFI rated 3.2A-1 or better mandatory
4. AMB 260x, MyLaps Flex or MyLaps X2 transponder mounted a minimum of 12" behind the rear axle on passenger side.

## **DRIVER SAFETY**

1. A quick release NASCAR approved type seat belt/shoulder harness/crotch belt minimum 16.1 SFI must be properly mounted.
2. Belts must be securely fastened to the roll bars. The belts must be dated and must be replaced at the conclusion of the 2nd year after manufacture.
3. A Hans device is mandatory.
4. S.F.I. Fire suits are mandatory.
5. A drop down window net is mandatory. Must be mounted in an appropriate manner.
6. Race cars must have an approved fire extinguisher securely mounted within reach of the driver.

## **ENGINE OPTIONS**

### **OPTION # 1: RIVERHEAD RACEWAY CRATE**

1. Weight 2775 - 58% left side weight
2. GM 604 Crate Engine will be used with a Holley 650 cfm, Part # 0-80541 carburetor and any 1" aluminum (only) spacer.
3. It is mandatory that ALL crate engines be purchased and sealed by Riverhead Raceway.  
All engines must remain as delivered by General Motors including: harmonic balancer, distributor, valve covers, springs, rocker arms, seals, etc.



4. It is strictly forbidden to tamper with the factory and/or RIVERHEAD RACEWAY seals in order to gain access to the internal workings of the engine. Anyone caught tampering with the factory and/or RIVERHEAD RACEWAY seals shall immediately have their engine confiscated by Riverhead Raceway and fined \$1,000.
5. These crate engines are considered to be non-rebuildable and non-repairable. In the event that an engine sustains internal damage or wear that requires removal of one or more seals, the engine is then said to have served its life and must be discarded and a new one obtained!
6. Any sale of a crate engine has to take place with a Riverhead Raceway Tech Official present.

### CARBURETOR

1. Stock Holley 650cfm, Part # 0-80541 is the only legal carburetor.

### BODY OF CARBURETOR

1. NO polishing, grinding, or drilling of holes permitted.

### BOOSTERS

1. Boosters may not be changed.
2. Size and shape of booster must not be altered.
3. Booster height must remain standard.

### VENTURI

1. Venturi area must not be altered in any way.
2. The casting ring must remain completely visible and may not be removed.

### BASE PLATE

1. Base plate must not be altered in size or shape
2. NO holes may be drilled in the base plate.



## BUTTERFLIES

1. Stock butterflies must not be thinned or tapered.

## THROTTLE SHAFT

1. The throttle shaft must remain standard and must not be thinned, cut, or nicked in any manner.

## CARBURETOR SPACER/GASKET

1. The carburetor spacer must be a maximum of one (1) inch thick.
2. Any aluminum spacer is allowed. NO sandwich type or insulator type gaskets permitted.
3. The maximum gasket thickness shall be .065.

## IGNITION SYSTEM

1. MSD Ignition Boxes 6AL #6420 and 6ALN #64306 are approved for use in ALL Engine Options
2. MSD distributor 85551, 85561, and 8570 as well as GM dist. 10093387 are approved for use in ALL Engine Options.
3. Magnetos permitted.
4. One (1) MSD control. Analog style only.
5. NO external rev limiter or timing control modules permitted.
6. NO traction control devices permitted.
7. When using a crank trigger device or similar component and a distributor, only one (1) of these components may be connected while competing. You may use either a crank trigger or the distributor. Connector(s) for these units must be accessible and visible at all times. If any of these components are found to be used together the car will be disqualified, parts confiscated and the driver will be disciplined.
8. All engines must use stock firing order.



### ENGINE OIL

1. Any type of combustion enhancing oils or additives are strictly prohibited.

### WATER PUMP/ALTERNATOR

1. Any serpentine, cog, or v-belt pulley system permitted.

### OPTION #2: LATE MODEL

1. Weight 2875 - 58% left side weight
2. Due to the limited availability of new Chevrolet bowtie heads, the Dart cast-iron head and World Products head is approved for use with NO weight penalty in the Late Model Division. Other mfg. heads will not be permitted.
3. The intake manifold mounting holes in the Dart head may not be plugged and relocated from their original position. A Fel-Pro part number 1205 intake manifold gasket is the only gasket permitted and must be unaltered. A stock Dart head will be available for our comparison. Any deviation to the intake mounting hole location or angle for our sample is not permitted.
4. All other cylinder head rules remain the same and pertain to all cylinder heads.

### ENGINE DISPLACEMENT

1. 360 cubic inches maximum.
2. The only Ford engine allowed is the 351 Cleveland.

### ENGINE BLOCK

1. The engine block must be of standard factory production with standard external measurements in all respects.
2. Cast iron blocks only. Dart (SHP) part # 31161111



## PISTONS/RODS

1. Any flat top piston may be used.
2. Valve reliefs may be cut into pistons.
3. NO portion of the piston may protrude above the top of the block.
4. Steel connecting rods ONLY.
5. NO aluminum, stainless steel or titanium rods allowed.

## CRANKSHAFT/BALANCER

1. Standard steel or cast iron production design crankshafts permitted.
2. Aftermarket steel crankshafts permitted.
3. Any bore/stroke combination permitted provided it does not exceed 360 cubic inches.
4. NO aluminum balancers permitted.

## OIL PAN

1. Wet sump only.
2. NO dry sumps or external oil pumps. Accusump system allowed.
3. A one inch inspection hole (such as those manufactured by Canton) Must be installed in the oil pan. The plug must be installed in a way as to not impede its use.

## CYLINDER HEAD

1. Cylinder heads must be of stock production only. Stock cast iron heads only.
2. Limit of two (2) valves per cylinder.
3. NO titanium or other lightweight valves permitted
4. External modifications will not be permitted.
5. NO spacers permitted between head and intake manifold. All cylinder heads must be approved by Riverhead Raceway.
6. The minimum valve angle is 20 degrees.
7. The use of GM Vortec or Ford SVO series heads is not permitted.





## **CAMSHAFT/VALVE LIFTERS/ROCKER ARMS**

1. Solid or hydraulic camshaft permitted.
2. No roller camshaft and/or lifters permitted.
3. No mushroom lifters permitted. Lifters must be similar in design as OEM.
4. Roller rocker arms permitted.

## **INTAKE MANIFOLD**

1. Any two (2) or four (4) barrel cast iron or aluminum manifold allowed.
2. No tunnel or cross ram manifolds permitted.
3. Must have a 3/32 hole drilled in the head each of 2 intake bolts (directly next to each other) on both sides of the intake.

## **CARBURETOR**

1. Stock R-4412 Holley two (2) barrel 500 cfm is the only legal carburetor.

### **Carburetor Jets**

1. Jets of any size may be used.

### **Body of Carburetor**

1. No polishing, grinding, or drilling of holes permitted.
2. Choke horn may be removed.

### **Boosters**

1. Boosters may not be changed.
2. Size and shape of booster must not be altered.
3. Booster height must remain standard.



### Venturi

1. Venturi area must not be altered in any way.
2. Casting ring must remain completely visible and may not be removed.

### Base Plate

1. Base plate not to be altered in size or shape. No holes drilled in the base plate.

### Butterflies

1. Stock butterflies must not be thinned or tapered.
2. Idle holes may be drilled in the butterflies.
3. Screw ends may be cut even with the shaft but the screw heads must remain standard.

### Throttle Shaft

1. The throttle shaft must remain standard and must not be thinned, cut, or nicked in any manner.

### Spacer/Gaskets

1. Only one (1) piece spacer, maximum one (1) inch in thickness, may be installed between the intake and the carburetor.
2. The spacer must have two (2) holes that match the base of the carburetor. Holes must be cut perpendicular with the base of the carburetor. NO taper or bevels.

### FUEL FILTER

1. NO plastic fuel filters allowed. NO additives may be added to fuel.



## IGNITION SYSTEM

1. MSD Ignition Boxes 6AL #6420 and 6ALN #64306 are approved for use in ALL Engine Options
2. MSD distributor 85551, 85561, and 8570 as well as GM dist. 10093387 are approved for use in ALL Engine Options.
3. Magnetos permitted.
4. One (1) MSD control. Analog style only.
5. NO external rev limiter or timing control modules permitted.
6. NO traction control devices permitted.
7. When using a crank trigger device or similar component and a distributor, only one (1) of these components may be connected while competing. You may use either a crank trigger or the distributor. Connector(s) for these units must be accessible and visible at all times. If any of these components are found to be used together the car will be disqualified, parts confiscated and the driver will be disciplined
8. All engines must use stock firing order.

## OPTION #3: CHARGER

1. Weight 2800 - 58% Left side weight

## ENGINE DISPLACEMENT

1. General Motors engines are allowed 350 cubic inches plus .045 inches overbore per cylinder.
2. Ford engines are allowed 351 cubic inches plus .045 overbore per cylinder.

## ENGINE BLOCK

1. The engine block must be of standard factory production with standard external measurements in all respects.
2. NO aluminum or bowtie blocks permitted.



## INTERNAL CHANGES

1. Internal polishing, porting, altering and/or relieving of engine parts is not permitted
2. NO coatings of any type are permitted on any part of the engine.
3. NO external crankcase evacuation devices permitted.

## PISTONS/RODS

1. Any flat top piston may be used.
2. Valve reliefs may be cut into pistons.
3. NO portion of the piston may protrude above the top of the block.
4. Aftermarket rods permitted. They must be a solid beam steel type sportsman rod.
5. Chevrolet must use 5.700 rods.

## CRANKSHAFT/BALANCER

1. Only standard steel or cast iron production design crankshafts permitted
2. Aftermarket crankshafts permitted. Minimum weight 48 lbs.
3. Stroke must be 3.48 inches. NO knife edge crankshafts permitted. NO pendulum undercutting permitted.
4. Only standard OEM type balancers are permitted. Aftermarket steel balancers are permitted. NO aluminum balancers permitted.
5. All crankshafts must maintain (350) main size and 2.100 rod journal size with a maximum of .030 undersize permitted.

## CYLINDER HEAD

1. Cylinder heads must be of stock production only.
2. No bowtie, aluminum, Dart II, or angle plug heads permitted
3. Limit of two (2) valves per cylinder.
4. No titanium or other lightweight valves permitted
5. No porting or polishing permitted.
6. External modifications will not be permitted.
7. Internal polishing, porting, and relieving is not permitted.



8. All heads are limited to a minimum 60cc combustion chamber.
9. No modifications to combustion chamber permitted, including unshrouding of intake or exhaust valve sides of chamber.
10. Basic three angle valve job permitted. The only angles permitted will be as follows:  
Top angle 30 degrees, Seat angle 45 degrees, Bottom angle 60 degrees
11. A 70- degree or greater angle below the bottom of the valve seat is not permitted.
12. The maximum grinding, cutting, or machining depth permitted will be limited to a maximum depth of .250 (1/4 ") as measured from the top of the valve seat.
13. When cutting the valve seat angles, NO stone or grinding marks are permitted above the bottom of the valve guide. All cutting in reference to the valve job must be centered off the centerline of the valve guide. Competition style multi-angle valve jobs are permitted. The bowl area must pass a 360 degree "ball" check (the appropriate sized ball must not fall into the guide area when rolling around on the valve stem). Intake is a .787" ball. Exhaust is a .531" ball. Surfaces and/or edges where the cutter or stone has touched must not be polished. NO hand grinding or polishing is permitted on any part of the head.
14. Valve guide and/or replacement liner permitted. Must remain in original location.
15. Cylinder heads must retain all factory stock as cast dimensions and configurations.
16. The use of the GM Vortec or Ford SVO series heads are not permitted.
17. Dart iron eagle s/s part number 10024266 and EQ cc167c2i cylinder head are permitted. Heads must be run in out of box condition, custom ordering of partial production/finishing is not permitted.
18. On all engines, only one standard flat gasket may be used between the head and the intake manifold. NO wedge type gaskets allowed.
19. NO metal spacers allowed.

### CAMSHAFT/VALVE LIFTERS/ROCKER ARMS

1. Solid or hydraulic camshaft permitted.
2. NO roller camshaft and/or lifters permitted.
3. NO mushroom lifters permitted.
4. Stock diameter lifters only for make of engine.
5. Lifters must be similar in design size/shape as original equipment.



6. Stud type 1.50 to one (1) ratio roller rocker arms are permitted.
7. OEM type timing chain only. NO gear or belt drives permitted.
8. NO stud girdles permitted.
9. Only steel valve spring retainers are permitted.
10. Shaft style rocker arm not permitted.

### INTAKE MANIFOLD

1. Absolutely NO modifications/alterations allowed. This includes: grinding, porting, polishing, etching, coating, painting, acid dipping, port machining, increasing port entry size, beveling, machining of the carburetor mounting surface.
2. All casting numbers, manufacturer's numbers and firing order must remain on manifold
3. The following aftermarket intakes may be used. All part numbers are current design
4. Edelbrock series intake manifolds:
  - a. CHEVROLET#2101
  - b. CHRYSLER#2176
  - c. FORD WINDSOR#2181
5. Intake Manifold must be approved by the Riverhead Raceway Tech Officials.
6. MUST have a 3/32 hole drilled in the head each of 2 intake bolts (directly next to each other) on both sides of the intake.

### CARBURETOR

1. Stock R-4412 Holley two (2) barrel 500 cfm is the only legal carburetor.

#### Carburetor Jets:

1. Jets of any size may be used.

#### Body of Carburetor:

1. No polishing, grinding, or drilling of holes permitted.



2. Choke horn may be removed.
3. Boosters may not be changed.
4. Size and shape of booster must not be altered.
5. Booster height must remain standard.

### Venturi

1. Venturi area must not be altered in any way.
2. Casting ring must remain completely visible and may not be removed.

### Base Plate:

1. Base plate not to be altered in size or shape. No holes drilled in the base plate.

### Butterflies

1. Stock butterflies must not be thinned or tapered.
2. Idle holes may be drilled in the butterflies.
3. Screw ends may be cut even with the shaft but the screw heads must remain standard.

### Throttle Shaft

1. The throttle shaft must remain standard and must not be thinned, cut, or nicked in any manner.

### Spacer/Gaskets

1. Only one (1) piece spacer, maximum one (1) inch in thickness, may be installed between the intake and the carburetor.
2. The spacer must have two (2) holes that match the base of the carburetor. Holes must be cut perpendicular with the base of the carburetor. NO taper or bevels.



## FUEL FILTER

1. No plastic fuel filters allowed
2. No additives may be added to fuel

## OIL PAN

1. Wet sump only. NO dry sumps or external oil pumps b. Accusump system allowed.
2. A one inch inspection hole (such as those manufactured by Canton) Must be installed in the oil pan. The plug must be installed in a way as to not impede its use.

## IGNITION SYSTEM

1. MSD Ignition Boxes 6AL #6420 and 6ALN #64306 are approved for use in ALL Engine OptionsMSD distributor 85551, 85561, and 8570 as well as GM dist. 10093387 are approved for use in ALL Engine Options.
2. Magnetos permitted.
3. One (1) MSD control. Analog style only.
4. NO external rev limiter or timing control modules permitted.
5. NO traction control devices permitted.
6. When using a crank trigger device or similar component and a distributor, only one (1) of these components may be connected while competing. You may use either a crank trigger or the distributor. Connector(s) for these units must be accessible and visible at all times. If any of these components are found to be used together the car will be disqualified, parts confiscated, and the driver will be disciplined.
7. All engines must use stock firing order.

## ENGINE LOCATION

1. The forward most spark plug must be located no further back than the centerline of the right and left upper ball joints. Any engine whose forward most spark plug is located behind the centerline of the right and left upper ball joint shall incur a (15) fifteen pound per inch penalty. That additional weight shall be mounted in front of the engine between the front frame rails.





## **WEIGHT RULES**

1. Factory sealed 604 crate engines purchased outside Riverhead Raceway Crate engine program are permitted using Option #2 weights. The weight rule is subject to change at any time with one weeks' notice to ensure that all engine types remain competitive with each other.
2. All cars must weigh according to the following engine options:

| OPTION #1    | OPTION #2    | OPTION #3    |
|--------------|--------------|--------------|
| CRATE 604    | LATE MODEL   | CHARGER      |
| Weight: 2775 | Weight: 2875 | Weight: 2800 |
| 58% Left     | 58% Left     | 58% Left     |

THESE WEIGHTS MAY BE ADJUSTED AS NEEDED TO KEEP ALL OPTIONS EQUAL

1. A time trial/impound race will require all cars to weigh 30 lbs more at pre-tech.
  - a. Crate: 2805 lbs,
  - b. Late Model: 2905 lbs
  - c. Charger: 2830 lbs
2. Added weight must be securely fastened with a minimum of two (2) bolts.
3. All added weight must be painted white with car number and division clearly marked.
4. Dislodged weight cannot be returned to the car for weighing after the race.
5. Car weighed with the driver in normal position with helmet on lap.
6. The base weight of the vehicle must be displayed on the right side of the hood in a contrasting color at least 2" tall.

## **BATTERY**

1. Battery must be securely fastened and properly covered.
2. Battery cannot be located in the drivers' compartment.
3. Battery and ignition shut off switches' mandatory.
4. Only one (1) 12-volt battery is permitted.



## **BRAKE COMPONENTS**

1. Hydraulic four (4) wheel brakes mandatory.
2. No carbon fiber parts permitted.
3. Each brake caliper may not exceed a racer net price of \$265.

## **CAR BODIES**

1. One exposed bar, both front and rear, must mount between the frame rails above the bumper for towing.
2. All cars must have complete bodies, hood, fenders, bumpers, and must be kept in a presentable condition. Original dimensions of all bodies must remain as manufactured.
3. Front bumper mount to be constructed with (1) 1  $\frac{3}{4}$ " dia tube extending from each frame rail to support (1) 1  $\frac{3}{4}$ " round tube bumper. Bumper tube must fit in the bumper cover.
4. No additional support from bumper/bumper supports to frame permitted.
5. One exposed bar, both front and rear, must mount between the frame rails above the bumper for towing. Bar should be 1 1/2" diameter and 24" maximum width. 1" tube on each side may project from grand national bars down to the front bumper.
6. Front and rear bumpers may not extend outside of bumper covers.
7. NO NERF BARS. Lexan body/decal protectors permitted.
8. Aftermarket sportsman, ABC and LMSC style bodies are permitted. No outlaw style bodies will be permitted. Bodies must meet tech visual approval. No carbon fiber bodies permitted.
9. Drive shaft tunnel may be raised a maximum of 10 inches measured from the driver's side floor to the top of the tunnel. The right-side floor will then project either directly across on a level plane or at an angle towards the top of the roll cage on the passenger side of the vehicle. This area is not to be boxed in.
10. Hood must have positive fasteners, left, right, and center. Also, two (2) positive type fasteners on the back of hood when hinges have been removed.



11. Trunk lid must be in operating condition with positive type fasteners.
12. All cars must have full floors and firewall constructed of 18 ga steel minimum.
13. All cars must have a rear tail panel.

### EXHAUST SYSTEM

1. Twelve (12) inch LOBAK and FloRite 3500 mufflers are the only mufflers approved for competition.
2. Headers are allowed but must remain inside frame rails. Extra brackets mandatory.
3. 180 degree headers are not permitted.
4. Crossover exhaust headers will be allowed, but must remain inside frame rails. The mufflers must be the last item on the exhaust system and must exit behind the doors.

### FUEL CELL

1. Fuel cell mandatory. NO ballast in fuel cells (lead, etc.) Fuel cell capacity may not exceed 22 gallons.
2. The cell must be protected with 1'x1'x1/8" square tubing in an "X" shape underneath the cell.
3. Fuel vent line and filler neck must be equipped with a check valve approved by NASCAR.
4. Fuel cells must be secured with 1" x 1/8" steel straps with a minimum of four (4) straps across the top of the cell.
5. Minimum ground clearance for fuel cells is six (6) inches.
6. Fuel shut off valve mandatory.
7. Electric fuel pumps and pressure systems are prohibited.
8. Must meet NASCAR specifications. It is highly recommended that the fuel cell bladder be
9. NO more than six (6) years old.



## **GAUGES**

1. Analog gauges only.
2. Digital type gauges are not permitted.

## **ELECTRICAL SWITCHES**

1. Electrical switches must be located within easy reach of the driver and be properly labeled.

## **HOOD**

1. Full hood is mandatory.
2. Hood scoop optional but must be sealed in the front.

## **MIRRORS**

1. Rear View mirror required. Rearview mirror must not extend outside of the car.
2. 1 left Side view mirror permitted with a maximum diameter of five (5) inches.
3. The mirror cannot extend outside the car.
4. The maximum size of the rearview mirror shall be 2 1/8" x 17 3/4"

## **RADIATOR AND FAN**

1. Radiator must remain stock appearing and remain in the stock mounting position.
2. All cars must have a radiator overflow can.
3. The use of antifreeze is prohibited. Electric fans permitted.
4. Fan shroud may be used but cannot extend more than one (1) inch behind the fan blade.

## **REAR END**

1. Locked rear ends are mandatory.



2. Quick change rear ends permitted.
3. Full floater rear end permitted.
4. Only aluminum or steel spools permitted.

## **ROLL CAGE**

1. Minimum size of roll cage tubing is 1  $\frac{3}{4}$ " (.095) thick. All cars must have an "X" type member across and behind the driver. Minimum four point cage required.
2. All bars within drivers reach must be padded.
3. All cars must have the trunk area sealed.
4. Four curved bars in driver's door with six (6) vertical bars (2 between each horizontal bar) and three (3) bars in the passenger door are mandatory.
5. It is mandatory to have 16 gauge metal welded between door bars or a 16 gauge plate 40" in length and 17" in high minimum, welded between the door bars and driver's door.
6. The total height of the roll cage shall be 40  $\frac{1}{2}$ " from the bottom of the frame. Halo to be NO less than 1" lower.
7. There must be a minimum 1-1/2 inch O.D .083 thickness tube welded either diagonally or perpendicular between the halo and the main hoop and another welded between the halo and the dash bar centered in the opening.
8. Minimum height of door bars shall be 22  $\frac{1}{2}$ " from bottom of frame.
9. A "Petty bar" is recommended between the center of the cage and upper right front halo.
10. Brain bar for head protection is mandatory and must be padded
11. Width of halo should be a minimum of 44" on perimeter chassis, and 32" on straight rail chassis. Measurement is from outside to outside of tubing.
12. ALL roll cage installations and workmanship **MUST** be acceptable to the Riverhead Raceway Track / Tech Officials.

## **SEATS**

1. Containment style seats are strongly recommended.



2. Seat MUST be an aluminum racing seat bolted to a steel frame, connected to the cage. Must have six (6) -3/8" bolts, grade 8 with minimum 2" dia washers securing the seat from inside. One (1) must be in each corner of the seat (2-3" from the outer edge) and two (2) in the headrest securing the seat to the upper support brace.
3. A support brace must be installed in the rear of the seat at shoulder height.
4. The support brace MUST be constructed from 1/8" thick steel plate minimum on the left side of the cage.

### **SPOILERS**

1. Front valance is permitted.
2. Rear spoilers are permitted, single plane only. Maximum 5 inches high by 60 inches wide.
3. Must be clear lexan and free of any decals, stickers, etc. Spoiler braces are permitted but must be located behind the spoiler. No braces, flanges, etc. in front of or alongside the spoiler.
4. Roof Rails will be permitted. Rails not to exceed one (1) inch in height and must follow the natural line of the roof.

### **STARTER**

5. Self-starters must be in working order.
6. All cars must start under their own power.

### **STEERING**

1. Steering box or rack & pinion steering permitted.
2. Quick release steel steering coupler required.



## **SUSPENSION**

### **SPINDLES, WHEEL BEARINGS, AND HUBS**

1. Front spindles must be linked to the frame using approved tether. One end of the cable with the large eye must wrap around the frame and pass through the smaller eye. The large eye of the cable must loop over the upper portion of the spindle.

### **FRONT SUSPENSION**

1. Coil over front suspension permitted but must mount to lower A-frame. b. Tubular upper A-frames permitted.
2. Tubular lower a-frames or struts permitted. Maximum 2 inch offset in lower a-frames or struts permitted. Stock lower-a-frames may also be used. Any front sway bar permitted.
3. Two (2) piece adjustable mono-ball upper ball joints permitted.

### **REAR SUSPENSION**

1. Coil over rear suspension permitted.
2. Rear spring position may be changed, but both rear springs must be located either inside or outside of frame rails.
3. Positively NO mechanical device allowed in order for the driver to shift weight while in motion. NO hydraulic weight-shifting devices permitted at any time

### **SHOCKS/SPRINGS**

1. Single Shock per Wheel.
2. No external canister shocks permitted



## GROUND CLEARANCE

1. Minimum ground clearance under the chassis is 4 inches.

## TRANSMISSION, DRIVELINE, AND CLUTCH

### Transmission

1. Standard transmission only.
2. Standard transmission must have at least two (2) forward and one (1) reverse gear in working order.
3. No quick gear change or S speed transmissions permitted.
4. Absolutely NO aftermarket transmissions allowed.
5. NASCAR approved scatter-shield required.

### Driveshaft

1. The driveshaft and universal joints must be similar in design to standard production.
2. Driveshaft must be steel and painted white.
3. Two (2) driveshaft straps required.

### Clutch

1. Multiple disc clutch permitted.
2. Only steel discs permitted.
3. The use of carbon fiber or other lightweight materials are not permitted.
4. Minimum clutch diameter will be 5 ½ inches.

## WHEELS AND TIRES

1. Track tire rule will be in effect and must be purchased at Riverhead Raceway.
2. Eight (8) inch or ten (10) inch rims permitted. All four(4) rims must be the same width on the car.
3. Steel wheels are mandatory. Any offset is okay.





4. The maximum allowable tread width, measured from the outermost part of the tire, both front and rear, shall be 79 inches.
5. Minimum length of wheelbase shall be 103.5".

### **WINDSHIELD**

1. A completely clear LEXAN windshield covering the entire windshield opening is mandatory.
2. A minimum of two (2) straps 1/8" x 1" must be installed inside the front windshield.
3. Rear window is optional. Must be clear LEXAN